



SEINEMASTER

The Notus Seinemaster is a wireless seine monitoring system. Its design is based on more than 25 years of experience. Notus has worked closely with customers to offer sensors that provide reliable, real time data and convenience of use. With our unique and reliable Activ-Omni Intelligence, Notus is the only net monitoring system to boast two-way communication, offering a complete view of the seine as it is being set and pursed, AND true omnidirectional capabilities, providing sensor data when it's needed most. The Notus Seinemaster provides optimal performance, for superior results.



OPTIMAL PERFORMANCE SUPERIOR RESULTS

The Notus Difference

Notus sensors boast an active, **two-way communication system**, not offered by other net monitoring systems. Instead of relying on traditional one-way pingers, Notus systems 'talk' to each other via proven two-way protocols. Using this reliable technology, Notus is the **ONLY** system capable of providing a complete view of the seine as it is being set and pursed. Depth of footgear and the distance from the vessel, combined, is information that is critical for deciding when to purse, and Notus is the

only system that provides distance.

Variable data rates:
5, 10, 20 and 60 second intervals

Notus is the only system to offer **true, omnidirectional pattern beams** in all of our net monitoring sensors. This proves to be vital when fishing in less than ideal conditions, when information is needed most.

With Notus Activ-Omni Intelligence, achieve optimal performance, for superior results.

SEINEMASTER

The Seinemaster provides answers by attaching small, robust sensors to the seine. All information is transmitted to the vessel wirelessly.



Sensors are installed just below the corkline and on the leadline. Just one sensor on the leadline provides depth of the seine, sink rate and range to the leadline. Up to three sensors can be added to the leadline.

Alignment sensors can also be installed just below the corkline. These sensors calculate the


alignment of the corkline with the leadline. This information is invaluable to ensuring fish do not escape.

A system consists of shipboard equipment (command unit, computer and hydrophone) that communicate wirelessly to sensors on the seine. Seinemaster displays all information in graphic and numeric form.

Omnidirectional full coverage. Data is provided as soon as sensors are in water.



SYSTEM SET UP & COMPONENTS



Command Unit

Capabilities: 1000 Code Capability
Frequency: 24 kHz
Serial Output to PC
Power: 120/240 VAC



Charger

Power: 120/240 VAC
Charge Time: 90 minutes
Charger: 1 to 4 sensors simultaneously



Seine Hydrophone

Beam Pattern: Omnidirectional
Output: 192 db Tx
Range: 700 m



Sensors (General specifications)

Range: Up to 2500+ m
Weight: 1.1 kg in water
Battery Capacity: Full Trip Capability
Deployable Depth: 1500 m

DEPTH AND ALIGNMENT SENSORS

J92N To Corkline 1 69.5Fa → + 3.4 m	A96N To Corkline 2 133.4Fa → + 17.4 m	I64N To Corkline 3 174.1Fa → + 3.5 m
C24D Leadline Depth 1 16.9Fa ↓ + 1.1 Fa/min	F44D Leadline Depth 2 21.6Fa ↓ + 0.7 Fa/min	H36D Leadline Depth 3 10.8Fa ↑ - 0.5 Fa/min
To Leadline 1 69.8Fa	To Leadline 2 125.8Fa	To Leadline 3 172.5Fa

Depth sensors indicate the distance from the ocean's surface to the sensor. Range from the vessel to the sensor is also provided.

- Depth information avoids pursing too soon
Depth is monitored in real time during the entire set, ensuring the seine is around fish before pursing
- Leadline depth will avoid costly hookups on the bottom
- Knowing depth permits catching fish very close to the bottom without touching the bottom
- Distance to the leadline (from the vessel) allows for the ability to see if currents are taking the leadline away from the vessel
- An optional temperature upgrade ensures the right temperature range for the targeted species, increasing catch quality





Alignment sensors (installed just below the corkline) indicate the alignment of the corkline and leadline.

- Fish escape when the leadline is behind the corkline
- To ensure maximum catch, the leadline should be in line or just in front of the corkline
- The above graphic indicates that the leadline (bottom of bars) is just in front of the corkline (top of bars)

SPECIFICATIONS

DEPTH AND ALIGNMENT SENSORS

**ACTIV
OMNI** | INTELLIGENCE



Sensors

Distance Range	Up to 2500+ m
Depth Accuracy	+/- 0.25% FS
Depth Resolution	+/- 0.1 m
Depth	Up to 2000 m
Temperature Accuracy	+/- 0.5° C
Temperature Resolution	+/- 0.1° C
Weight	1.1 kg in water
Battery Capacity	Full Trip Capability
Deployable Depth	1500 m

NOTES



NOTUS

For videos, photos, brochures, trawl tools and more,
please go to www.notus.ca

Videos
Photos
Brochures
Trawl Tools



NOTUS

www.notus.ca

Notus Electronics Ltd

391 Empire Ave
St. John's, NL, A1E 1W6
Canada
Tel: + 1 709 753 0652
Fax: + 1 709 753 0651
notus@notus.ca
www.notus.ca

Notus Maritima S.L.

Oficina D10, Zona Franca
Vigo, 36208
Spain
Tel: + 34 6977 15 901
Fax: + 34 9862 48 518
notus@notus.ca
www.notus.ca